

LPG PACKAGE TANK

용량별 구성

Specification & Dimension

1. LPG Tank : 0.5 / 1.0 / 1.99 / 2.99 / 2.45Ton(4.9Ton)
2. Capacity : 0.5Ton_1,237L / 1.0Ton_2,473L / 1.99Ton_4,737L / 2.99Ton_7,227L / 2.45Ton_6,107L
3. Vaporizer : 50kg/h, 100kg/h, 200kg/h, 300kg/h, 400kg/h, 500kg/h
4. Regulator : 50kg/h, 100kg/h, 200kg/h, 300kg/h, 400kg/h, 500kg/h
 - Mid Pressure Regulator : 0.57 ~ 0.83kg/h
 - Low Pressure Regulator : 2.8Kpa(50K, 100K, 150K, 200K)
 - Semi Low Pressure Regulator : 25Kpa(50K, 100K, 200K)
5. Main Glove Valve Applied
6. R-Tank Flexible Type & Piping Connection, Double Connection Applicable(Optional)
7. Natural Vaporizer Single/Double(Optional)
8. Bulk Coupling for Liquid/Vapor
9. Float Type Level Gauge
10. Pressure Gauge
11. Cabinet Box : SUS304



용도 : 소량으로 가스를 사용하고자 하는 APT, 산업체, 임대형으로 제작된 LPG공급설비
 Application : It is using for companies and apartment which use small quantity of LPG.

- * 1. 상기 사항은 벨크로리형이며 사용량에 따라 기화기 및 압력조정기가 선택된다.
 The above is for bulk lorry, and vaporizer and regulator is to be chosen according to using capacity.
- * 2. 내압폭발형 판넬부착가능(선택사항) Explosion proof panel can be installed upon requirement(option)
- * 3. 임대형으로 한국가스안전공사 검사필한후 출고. (선택사항) As package system, it has to be supplied after being approved by KGS (option)
- * 4. 탱크로리형을 요구시 펌프, 로리호스등 추가 (금액 및 사양변경) When requesting the system for tank lorry, pump and lorry hose are to be included additionally (specification will be changed)

